

XBO DHP for digital cinema projection

Lâmpadas xênon e arco curto




Áreas de aplicação

- Cinema projection

Características do produto

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



Ficha técnica da família de produto

Dados técnicos

Descrição do produto	Dados Elétricos		Dimensões e peso			
	Potência nominal	Amplitude de corrente	Diâmetro	Comprimento	Comprimento da base excluindo os pinos	Comprimento do cabo de entrada
XBO 1200 W/DHP OFR	120000 W	41...63 A	465 mm	3450 mm	295,00 mm	130 mm
XBO 1600 W/DHP OFR	160000 W	57...86 A	465 mm	3450 mm	295,00 mm	130 mm
XBO 2000 W/DHP L OFR	200000 W	64...95 A	550 mm	3450 mm	295,00 mm	130 mm
XBO 2200 W/DHP OFR	220000 W	68...95 A	520 mm	3450 mm	295,00 mm	130 mm
XBO 2500 W/DHP OFR	250000 W	63...95 A	550 mm	3450 mm	295,00 mm	130 mm
XBO 3000 W/DHS OFR	300000 W	77...113 A	600 mm	3420 mm	302,00 mm	155 mm
XBO 3000 W/DHP OFR	300000 W	77...113 A	550 mm	3450 mm	295,00 mm	130 mm
XBO 3000 W/DHP L OFR	300000 W	76...111 A	600 mm	3450 mm	295,00 mm	130 mm
XBO 4000 W/DHP L OFR	400000 W	95...137 A	600 mm	3450 mm	295,00 mm	130 mm
XBO 4000 W/DHP LL OFR	400000 W	95...137 A	600 mm	3450 mm	295,00 mm	130 mm
XBO 4000 W/DHP OFR	420000 W	91...130 A	600 mm	3450 mm	295,00 mm	130 mm
XBO 4500 W/DHP OFR	450000 W	108...155 A	600 mm	4360 mm	393,00 mm	155 mm
XBO 4500 W/DHP L OFR	450000 W	108...155 A	600 mm	4360 mm	393,00 mm	155 mm
XBO 6000 W/DHP OFR	600000 W	131...174 A	780 mm	4360 mm	393,00 mm	155 mm
XBO 6000 W/DHP L OFR	600000 W	125...160 A	780 mm	4360 mm	393,00 mm	155 mm
XBO 6000 W/DHP XL OFR	600000 W	125...160 A	7800 mm	4360 mm	393,00 mm	155 mm
XBO 6500 W/DHP OFR	650000 W	133...173 A	780 mm	4360 mm	393,00 mm	155 mm
XBO 6500 W/DHP L OFR	650000 W	133...173 A	780 mm	4360 mm	393,00 mm	155 mm
XBO 6500 W/DHP XL OFR	650000 W	133...173 A	780 mm	4360 mm	393,00 mm	155 mm
XBO 6500 W/DHP IX OFR	650000 W	133...173 A	785 mm	4360 mm	393,00 mm	155 mm
XBO 7000W/DHP OFR	700000 W	130...175 A	780 mm	4360 mm	393,00 mm	155 mm

Descrição do produto	Comprimento do centro luminoso (LCL)	Peso do produto	Comprimento do cabo	Distância entre eletrodos	Temperaturas e condições de funcionamento
					Máx temp amb admissível - ponto pinch
XBO 1200 W/DHP OFR	123,0 mm ¹⁾	48500 g	1300	3,5 mm	230 °C
XBO 1600 W/DHP OFR	123,0 mm ¹⁾	48500 g	1300	3,5 mm	230 °C
XBO 2000 W/DHP L OFR	123,0 mm ¹⁾	53000 g	1300	4,5 mm	230 °C
XBO 2200 W/DHP OFR	123,0 mm ¹⁾	53400 g	1300	3,7 mm	230 °C
XBO 2500 W/DHP OFR	123,0 mm ¹⁾	55800 g	1300	4,5 mm	230 °C
XBO 3000 W/DHS OFR	145,0 mm ¹⁾	59100 g	1550	6,0 mm	230 °C
XBO 3000 W/DHP OFR	123,0 mm ¹⁾	58100 g	1300	4,5 mm	230 °C
XBO 3000 W/DHP L OFR	123,0 mm ¹⁾	62300 g	1300	5,0 mm	230 °C
XBO 4000 W/DHP L OFR	123,0 mm ¹⁾	64500 g	1300	6,0 mm	230 °C
XBO 4000 W/DHP LL OFR	123,0 mm	64500 g	1300	6.3 mm	
XBO 4000 W/DHP OFR	123,0 mm ¹⁾	67000 g	1300	6,0 mm	230 °C
XBO 4500 W/DHP OFR	170,5 mm ¹⁾	85300 g	1550	6,0 mm	230 °C

Ficha técnica da família de produto

					Temperaturas e condições de funcionamento
Descrição do produto	Comprimento do centro luminoso (LCL)	Peso do produto	Comprimento do cabo	Distância entre eletrodos	Máx temp amb admissível - ponto pinch
XBO 4500 W/DHP L OFR	170,5 mm ¹⁾	85300 g	1550	6,0 mm	230 °C
XBO 6000 W/DHP OFR	170,5 mm ¹⁾	100000 g	1550	7,5 mm	230 °C
XBO 6000 W/DHP L OFR	170,5 mm ¹⁾	105000 g	1550	7,5 mm	230 °C
XBO 6000 W/DHP XL OFR	170,5 mm ¹⁾	100000 g	1550	8,0 mm	230 °C
XBO 6500 W/DHP OFR	170,5 mm ¹⁾	102300 g	1550	7,5 mm	230 °C
XBO 6500 W/DHP L OFR	170,5 mm ¹⁾	102300 g	1550	8,0 mm	230 °C
XBO 6500 W/DHP XL OFR	170,5 mm ¹⁾	102300 g	1550	8,0 mm	230 °C
XBO 6500 W/DHP IX OFR	170,5 mm ¹⁾	100000 g	1550	8.1 mm	230 °C
XBO 7000W/DHP OFR	170,5 mm ¹⁾	102300 g	1550	7,5 mm	230 °C

Descrição do produto	Espectativa de Vida		Informação adicional do produto	
	Vida mediana	Service Warranty Lifetime	Anodo (designação standard)	Catodo (designação standard)
XBO 1200 W/DHP OFR	3000 h	3800 h	SFaX30-14	SFc30-16
XBO 1600 W/DHP OFR	3000 h	3800 h	SFaX30-14	SFc30-16
XBO 2000 W/DHP L OFR	3300 h	3500 h	SFaX30-14	SFc30-16
XBO 2200 W/DHP OFR	1500 h	2000 h	SFaX27-14x80	SFc27-16/55
XBO 2500 W/DHP OFR	1700 h	2000 h	SFaX27-14x80	SFc27-16/55
XBO 3000 W/DHS OFR	1500 h	2000 h	SFaX27-9.5	SFa27-7.9
XBO 3000 W/DHP OFR	1500 h	1900 h	SFaX27-14x80	SFc27-16/55
XBO 3000 W/DHP L OFR	1900 h	2100 h	SFaX27-14x80	SFc27-16/55
XBO 4000 W/DHP L OFR	1300 h	1500 h	SFaX27-14x80	SFc27-16/55
XBO 4000 W/DHP LL OFR	1500 h	1900 h	SFaX27-14x80	SFc27-16/55
XBO 4000 W/DHP OFR	1100 h	1400 h	SFaX27-14x80	SFc27-16/55
XBO 4500 W/DHP OFR	1000 h	1300 h	SFaX30-9.5	SFa30-7.9
XBO 4500 W/DHP L OFR	1300 h	1500 h	SFaX30-9.5	SFa30-7.9
XBO 6000 W/DHP OFR	650 h	800 h	SFaX30-9.5	SFa30-7.9
XBO 6000 W/DHP L OFR	900 h	1100 h	SFaX30-9.5	SFa30-7.9
XBO 6000 W/DHP XL OFR	1000 h	1200 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP OFR	500 h	750 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP L OFR	700 h	800 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP XL OFR	900 h	1000 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP IX OFR	1000 h	1200 h	SFa30-7.9	SFaX30-14
XBO 7000W/DHP OFR	400 h	500 h	SFaX30-9.5	SFa30-7.9

Descrição do produto	Atributos		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Resfriamento	Posição de funcionamento	Date of Declaration	Primary Article Identifier
XBO 1200 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	05-03-2024	4008321396433 4052899497962 4062172030472

Ficha técnica da família de produto

	Atributos		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Descrição do produto	Resfriamento	Posição de funcionamento	Date of Declaration	Primary Article Identifier
XBO 1600 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4052899254831 4062172030465
XBO 2000 W/DHP L OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4052899275638 4062172030427
XBO 2200 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4008321865489 4062172030373
XBO 2500 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4008321821706 4052899010413 4062172030380
XBO 3000 W/DHS OFR	Arrefecimento forçado	s15/p15 ²⁾	05-03-2024	4008321199065 4008321330017 4062172030540
XBO 3000 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	05-03-2024	4008321309532 4008321330048 4008321865496 4052899091818 4052899096073 4052899195783 4052899287785 4052899468191 4062172030410
XBO 3000 W/DHP L OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4052899212886 4052899235908 4052899317277 4062172030502
XBO 4000 W/DHP L OFR	Arrefecimento forçado	p15/s15 ²⁾	06-03-2024	4052899212879 4052899235915 4052899468214 4062172030403
XBO 4000 W/DHP LL OFR	Arrefecimento forçado	p15/s15 ²⁾	07-03-2024	4062172114080
XBO 4000 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	05-03-2024	4008321309686 4008321546272 4008321865526 4052899091825 4052899096080 4052899195790 4052899287792 4052899317208 10046135694810 4062172030397
XBO 4500 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	05-03-2024	4008321199072 4008321633422 4062172030571
XBO 4500 W/DHP L OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4052899343344 4062172030588
XBO 6000 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	05-03-2024	4008321549693 4052899144026 4062172030663

Ficha técnica da família de produto

	Atributos		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Descrição do produto	Resfriamento	Posição de funcionamento	Date of Declaration	Primary Article Identifier
XBO 6000 W/DHP L OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4052899087088 4052899343405 4062172030670
XBO 6000 W/DHP XL OFR	Arrefecimento forçado	s15/p15 ²⁾	07-03-2024	4062172110839
XBO 6500 W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	05-03-2024	4008321676078 4062172030731
XBO 6500 W/DHP L OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4052899448636 4062172030755
XBO 6500 W/DHP XL OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4052899593640 4062172031684
XBO 6500 W/DHP IX OFR	Arrefecimento forçado	h90 ²⁾	07-07-2023	4062172363792
XBO 7000W/DHP OFR	Arrefecimento forçado	s15/p15 ²⁾	06-03-2024	4062172031707

Descrição do produto	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XBO 1200 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	f6cc71e9-adae-4c95-afe0-07d36b5e74f6
XBO 1600 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ddc0ca29-d545-4244-bd3d-01657e49e316
XBO 2000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3cc8eb7d-934b-482f-ade0-0afdb83ac51b
XBO 2200 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5e903ee1-3cc9-40f0-ae95-0a54da9c2b3a
XBO 2500 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2699a8c3-f6d1-4519-a2c4-83464e509907

Ficha técnica da família de produto

Descrição do produto	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XBO 3000 W/DHS OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0ad1e6ac-a107-4e86-a73c-0a8cdc49edb4 468df0c2-2da9-47b4-a001-357079e3d0c0
XBO 3000 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	A303E60B-72E8-4104-9C0C-1F16ADEED959 2C70619C-7452-40E1-9F11-72C36A77558D 34a49bce-cf7a-477b-8d7b-991718631ed4
XBO 3000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	42b5a623-65c3-4fc7-b272-e9973ba1c9ec
XBO 4000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a182c938-75ef-44e7-a0e6-e8e301002b19 ee6fe08d-465e-439d-9156-a1830163f87d
XBO 4000 W/DHP LL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	68536058-a0f0-4f39-8967-a173bfd19c5b
XBO 4000 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ce588d4a-f4ef-4dda-8e54-ddab4457e440 56ff5a8b-6ea4-41c2-bd17-d898f6c185d1
XBO 4500 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	012f940f-18dd-409c-9473-04140360c548
XBO 4500 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3de76945-7771-4e03-9280-550799b927c9

Ficha técnica da família de produto

Descrição do produto	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XBO 6000 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	8566eac2-b860-4860-9c27-f7b8e2871b1f
XBO 6000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e1be3907-8f4f-4d48-b496-86874180bac4
XBO 6000 W/DHP XL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e98aa7da-cb44-4008-ab03-b605fac43791
XBO 6500 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	412959b3-e26e-4a82-89ba-3ce9a6fa908b
XBO 6500 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	326fc61e-87e5-491e-a54a-876602402f4a
XBO 6500 W/DHP XL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0afbcb5a-721a-4942-bd3d-6024b2eff6a3
XBO 6500 W/DHP IX OFR				In work
XBO 7000W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	885c4405-74b6-4820-817d-399a936e4918

1) Distância do final da base até a ponta do eletrodo (frio)
2) Para funcionamento na posição de queima vertical: ânodo (+) no topo

Ficha técnica da família de produto

Instruções de segurança

Devido à sua alta luminosidade, radiação UV e pressão interna tanto no estado quente quanto no frio, as lâmpadas XBO só podem ser operadas em cápsulas de lâmpadas fechadas especialmente construídas para esse fim. Lâmpadas xênon são altamente explosivas. Quando quentes, elas podem causar marcas de queimaduras. Eles só devem ser manuseados quando a lâmpada está em temperatura ambiente. Use sempre as jaquetas protetoras fornecidas ao manusear essas lâmpadas. Ao embalar as lâmpadas e ao instalar ou remover as lâmpadas sem suas jaquetas protetoras, use sempre roupas de proteção (escudo facial com protetor de pescoço, jaqueta protetora e luvas resistentes e sem fiapos). Para obter mais informações, consulte os folhetos informativos relevantes e as instruções de operação.

Informações sobre aplicações

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

Retratação

Sujeito a alteração sem prévio aviso. Sempre utilize a versão mais recente.