

## LINEARlight FLEX Protect ADVANCED

– Módulos LED para aplicações profissionais e industriais



### Características do produto

- Fita de LED flexível e cortável
- Tipo de proteção: IP67
- Fine White (3.5 SDCM)
- A prova de névoa salina

### Benefícios do produto

- Muito longa para faixas de luz contínuas
- Grande liberdade no design graças à flexibilidade e divisibilidade do módulo
- Silicone de alto desempenho para vida extremamente longa e flexibilidade
- Conexão simples graças aos conectores pré-montados
- Design extraordinário com materiais de alta qualidade
- Conexão sem uso de ferramenta com o CONNECTsystem opcional
- Fácil montagem em muitas superfícies lisas devido à fita autocolante na parte de trás

### Áreas de aplicação

- Iluminação com sancas
- Integração na parede
- Corrimãos e corredores
- Iluminação de máquinas
- Iluminação de caminho
- Sinalização
- Adequado para uso externo

## Ficha técnica da família de produto

---

### Equipamento / Acessórios

- Ligação simplificada compatível com acessório opcional CONNECTsystem
- Instalação rápida com SLIM TRACK System otimizado
- Combinação perfeito com reatores OPTOTRONIC de 24 V

---

### Informações sobre aplicações

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

---

### Texto ficha técnica

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

---

### Vendas e suporte técnico

Vendas e suporte técnico [www.osram.br](http://www.osram.br)

---

### Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

# Ficha técnica da família de produto

## Retratação

Sujeito a alteração sem prévio aviso. Sempre utilize a versão mais recente.