

Product family datasheet

LEDiving BASIC R5W



Product family datasheet

Technical data

Product description	Electrical Data					Photometric Data
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux
LEDiving BASIC \pm R5W	0.96 W	12 V	0 W	± 20 %	13.5 V	55 lm

Product description	Physical Attributes & Dimensions			Lifetime Data
	Lamp base	Length	Diameter	Lifespan B3
LEDiving BASIC \pm R5W	BA15s	29.0 mm	19.0 mm	2000 hr

Product description	Lifespan Tc	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
		Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDiving BASIC \pm R5W	2000 hr	4052899463332 4052899414556 4052899463127 4052899414532	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDiving BASIC \pm R5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	12c61241-8e84-49d2-aad6-61ee9185fc4c a74edd59-fe84-466f-9e9c-d76036657cbc 4deab8c0-c089-4d6a-90f4-3738f5af799e e8c7bd92-d6cb-4cf2-9e8f-8360bae74918 eb08c6c5-5573-4254-af17-5f6a4f492b5f

Product family datasheet

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

