

LEDDriving HL EASY H10

LED replacement for conventional lamps



Cool White color temperature of 6,000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



Superior brightness

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



Ultra compact LED replacement for conventional H10 lamps as socket solution

Easy installation with optimized compatibility



New OSRAM LED lamps to increase safety and performance

The latest generation of OSRAM LED lamps provides an even more convenient solution in order to replace and upgrade existing halogen lamps: With its ultra compact dimensions, the OSRAM LEDDriving HL EASY provides optimized compatibility as well as easy plug & play installation. Upgrading with state-of-the-art LED technology and a color temperature of 6,000 K for a stylish cool white look as well as improved visibility. Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for

information on your country.

Product family datasheet

Technical data



| Product description | Electrical Data | | | | Photometric Data |
|------------------------|-----------------|-----------------|-----------------|--------------|-----------------------|
| | Power input | Nominal voltage | Nominal wattage | Test voltage | Nominal luminous flux |
| LEDriving FL \pm H10 | 9.43 W | 12 V | 8 W | 13.5 V | 720 lm |

| Product description | Luminous flux tolerance | Physical Attributes & Dimensions | Lifetime Data | | Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|------------------------|-------------------------|----------------------------------|---------------|-------------|--|
| | | Diameter | Lifespan B3 | Lifespan Tc | Primary article identifier |
| LEDriving FL \pm H10 | ± 15 % | 17.2 mm | 2500 hr | 5000 hr | 4052899605060 4062172401913 4062172033329 |

| Product description | Candidate list substance 1 | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|------------------------|----------------------------|------------------------|--|--|
| LEDriving FL \pm H10 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 5bb0763b-d3d5-4ad4-9acb-80e77f971c23 b86477a2-9ace-40c3-a83c-07c2a8a5ba94 1d54fd7a-44a9-43a5-b0fd-acb4b3cbf3a7 df34dec2-e5d8-4f51-8a1c-a3c24fb12f06 5114875c-f327-4bd9-8308-3aa281a00817 |

Product family datasheet

Download Data

| File | |
|---|---|
|  | User instruction GPRS_Safety symbols instructions |
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information. Detailed guarantee terms can be found at www.osram.com/am-guarantee.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

