Product family datasheet



Lightbar SX300-SP

Powerful and durable LED auxiliary light for safe driving pleasure





Compact housing design Compact mounting dimensions enables a wide range of possible applications



Lighting distance up to 270 meters Increased far field illumination



Spot Beam Highly concentrated light beam



Vibrant LED light for more safety on the road

Unlit streets and dirt roads always present a greater risk for accidents. The LEDriving Lightbar SX300-SP LED auxiliary light not only shines more light in the darkness, it also increases safety in traffic.

The LED auxiliary light with approval for use on roads is equipped with 12 high-performance LEDs and gives drivers better visibility. The perception of light is also enhanced for oncoming traffic. The search light therefore contributes to this aspect of road safety.

Drivers can identify obstacles or potential hazards far in advance thanks to the beam range of the automotive auxiliary light. With an illuminance of one lux, the beam of light can reach up to 270 meters with a beam angle of eight degrees.

The intelligent reflector design of the LED high beam provides extremely high optical efficiency with

homogeneous light distribution. This means that oncoming traffic is exposed to less glare from the 2600 lumen LED light.

Along with strong light output and improved road safety, the search light also offers visual appeal: It further enhances the unique off-road look of the vehicle.

Ruggedness and durability for on and off-road use

Strong jolts and harsh weather conditions present major challenges for the material. To ensure a longer lifespan, the LED auxiliary light is therefore equipped with a hard-wearing polycarbonate lens that meets the toughest demands.

The LEDriving Lightbar SX300-SP LED auxiliary light works dependably even at extreme temperatures of -30 to 60 degrees Celsius. That makes it the ideal companion, especially for off-road driving.

The integrated driver and thermal management system protects the high-performance LEDs from possible overheating. In addition, over and under voltage protection prevents power from exceeding a defined current over a certain amount of time.

Compact mounting dimensions mean that the LED auxiliary light can be used in a wide range of applications. Not only 4x4 and off-road vehicles, but utility and industrial vehicles can also benefit from the increased light output of the LED auxiliary light.

Product family datasheet

Technical data

	Product information	General Produce Information	ct	Electrical Data		Photom etric Data
Product description	Application (Category and Product specific)	Global order reference		Nominal wattage	Test voltage	Nominal luminou s flux
Lightbar SX300-SP	Additional high beam application	LEDDL106-SP		29 W	13.5 V	2600 lm
	Lifetime Data	Capabilities	Certific	ates & standards		
Product description	Lifespan Tc	Technology Approval marks – Type of protection approval				
Lightbar SX300-SP	5000 hr	LED	E4 appr	roval IP69K		
				Logistical data	Environme Regulator Informatic Informatic according EU Regula 1907/200	y on Art. 33 of tion (EC)
Product description	Standards	ECE reference number		Commodity code	Primary ar identifier	ticle
		20		85122000900	40528995	

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
Lightbar SX300-SP	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow	0436cd83-27e5- 4abc-b659- 9b1ba1bd2493 ff87f5b2-63c7-4c37-
			safe use of the article.	a933-39ed1976d1eb

Product family datasheet

Download Data

	File
	User instruction LEDriving Lightbar
	User instruction GPRS_Safety symbols instructions
D	Movie application LEDriving D and W Image Video Bringing light to life (EN)
D	Movie application Working and Driving Lights Amarok Winter
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application LEDriving driving & working lights in application (EN)
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
D	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
D	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
Ľ	ref_pim_amsp_product360degreeimages Lightbar SX300-SP 360° Image

Legal advice

In vehicles with 12/24 volts, auxiliary lights must be installed in pairsPrecise terms and conditions at: www.osram.com/guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.









