## **OSRAM**

# BATTERYcharge SOLAR 200W





Works In overcast conditions Doesn't require direct sunlight to provide power



Suitable for 12V leisure batteries With over-charge protection and 200W power delivery, ideal for seasonal vehicles



IP65 water resistance Designed to handle outdoor conditions with ease



### High-Performance 200W Solar Panel for Reliable Off-Grid Power

The OSRAM BATTERYCharge SOLAR 200W is a highperformance, portable solar panel designed to charge and maintain 12V leisure batteries. Featuring mono-crystalline solar panels in a robust aluminum frame, it delivers up to 200W of free solar power, suitable for caravans, campervans, RVs, and outdoor use.

With a 12V/20A charge controller and USB output, it prevents overcharging while allowing you to also charge small devices. Its IP65 water-resistant design and sturdy aluminum stand ensure durability, while the plug-and-play setup makes it easy to use. Lightweight and foldable, it's ideal for off-grid adventures, even in overcast conditions. Comes with a 5 m battery lead and connecting clamps for

immediate use.

#### Technical data

	Product information	General Product Information	Electrical Data	
Product description	Application (Category and Product specific)	Global order reference	Charge Rate (Up to)	Maintainance Charge (up to)
BATTERYcharge SOLAR 200W	Solar battery maintainer	OHPS200	N/A	9.9 A

		Physical Attributes & I		Dimensions
Product description	Max battery capacity	Min battery capacity	Length	Width
BATTERYcharge SOLAR 200W	N/A Ah	n/a	801.0 mm	40.0 mm
		Dimensions & weight		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Height	Power Cable Length	Clamps Cable Length	Candidate list substance 1
BATTERYcharge SOLAR 200W	700.0 mm	10.8 m	1.0 m	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
BATTERYcharge SOLAR 200W	7439-92-1	The identification of	6264e1b6-8329-
		the Candidate List	4688-ae3e-
		substance is	97063604c835
		sufficient to allow	
		safe use of the	
		article.	

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.