

LEDDriving SL P21/5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P21/5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21/5W

LEDDriving SL P21/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information		General Product Information	Electrical Data	
Product description	Application (Category and Product specific)	Product type (off-road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDriving SL \triangleq P21/5W	Mainly used for signal/ indicator applications	Off-road \triangleq P21/5W	7528DWP	2.50 / 0.5 W	12 V

				Photometric Data	Physical Attributes & Dimensions
Product description	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux	Lamp base
LEDriving SL \triangleq P21/5W	1 W	$\pm 25\%$	13.5 V	145/30 lm	BAY15d

				Lifetime Data	
Product description	Length	Diameter	Diameter	Lifespan B3	Lifespan Tc
LEDriving SL \triangleq P21/5W	52.5 mm	27.0 mm	27.0 mm	1500 hr	4000 hr

	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDriving SL \triangleq P21/5W	LED ¹⁾	4062172151726 4062172401197	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving SL \triangleq P21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	026eb835-3aa5-4bfa-a635-bb4b42c468ab

¹⁾ Light-emitting diode lamp

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.