

LF -4PIN Protect - Installation Kit

RGB 4pin LINEARlight Flex IP67 Connector | Accessories for Flexible LED strips

Características do produto

- Quick and easy installation
- Compatible with TEC Flex




Benefícios do produto

- Instalação simples, sem necessidade de ferramentas ou solda (CONNECTsystem)
- Tempo de instalação reduzido (CONNECTsystem)
- Pode ser conectada na frente do módulo ou nos pontos de divisão (CONNECTsystem)
- Perfil baixo (CONNECTsystem)

Ficha técnica do produto

Dados técnicos

Dimensões e peso



Comprimento	300 mm
Peso do produto	2000 g
Secção do cabo, primário	1,4 mm ²
Largura	198 mm
Altura	134 mm

Informação adicional do produto

EAN sucessor	4062172016490
EAN sucessor	4008321977076

Dados logísticos

Código do material	854442909000
--------------------	--------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	30-08-2022
Primary Article Identifier	4008321977076 4062172016490
Declaration No. in SCIP database	In work

Download Data

Arquivo	
	Brochuras Light is freedom of design (EN)

Ficha técnica do produto

	Brochuras CONNECTION System for LINEARlight FLEX and TEC Flex IP00 - Quick installation guide
---	--

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Dados de Logística

Código do produto	Descrição do produto	Embalagem unitária (peças/unidade)	Dimensões (comprimento x largura x altura)	Volume	Peso bruto
4008321977076	LF -4PIN Protect - Installation Kit		570 mm x 150 mm x 340 mm	29.07 dm³	1897.00 g

O código do produto mencionado indica a quantidade mínima a ser adquirida. Uma caixa unitária pode conter um ou mais produtos. Quando for colocar o pedido de compras, indique uma quantidade unitária ou múltiplos da caixa unitária.

Retratação

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.