# **OSRAM**

# TYREinflate Connect 650



# **Download via App**

The smart app stores the tyre pressure for your car and downloads it to the OSRAM TYREinflate Connect 650



# **Auto Stop function**

Auto Stop function when preset pressure is reached.



#### **Leak Detection**

Including function to detect a loss of tyre pressure



#### **OSRAMconnect**

Connecting you with your car



# OSRAMconnect App compatible tyre inflator

Improve your driving performance and fuel costs by making sure your tyre pressure is correct. The OSRAM TYREinflate Connect 650 is a digital tyre inflator compatible with the OSRAMconnect app, with a backlit display for easy and accurate pressure measurement and inflation<sup>3)</sup> of tyres, showing pressure values in BAR, kPA and PSI. The app can store up to 5 vehicles and the associated information and has a function to detect a loss of tyre pressure. Furthermore, the OSRAM TYREinflate Connect 650 has an automatic switch-off function as soon as the preset pressure is reached. In addition, it has a storage compartment for valve caps, a 3.3 m long retractable power cable with a 12V fuse plug, a 65 cm long flexible air hose with an easily accessible holder and an additional LED light for illumination at night or in poor lighting conditions and a large on/off switch for additional manual operation. An inflation time of about 3 minutes<sup>2)</sup> gets you on the road and where you need to be fast. Also included is a 3-piece adapter set, for bikes, balls and other inflatables, and a durable storage bag. OSRAM provides a 2-year guarantee on this product 1)

1) For precise conditions please refer to: www.osram.com/am-guarantee

2) Based on inflating a 13" tyre from flat to 2.41 BAR

3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

# Product family datasheet

# Technical data

	Electrical Data	Additional product data	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Nominal voltage	Display Type	Fuse	Primary article identifier
TYRE inflate Connect 650	11.1 V	Digital	10 A	4052899622883

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
TYRE inflate Connect 650	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	f2f01f10-b494-4e57- ad3c-e7f344875985

# Product family datasheet

### Download Data

### File



User instruction TYREinflate Connect 650

# Safety advice

Reaches a maximum noise level of 90 db.

- Legal advice
  1) For precise conditions please refer to: www.osram.com/am-guarantee
- <sup>2)</sup> Based on inflating a 13" tyre from flat to 2.41 BAR
- $^{3)}$  Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyresApplication advice:For more detailed application information and graphics please see product datasheet and the user instruction.

# **Application advice**

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.