


LEDDriving™ HL EASY XEN D3S



Easy plug & play installation

Accurate mechanical compatibility – no adapters and/or caps needed



Compact LED replacement for conventional high and low beam lamps

Same geometry as HID - allowing high compatibility with plenty of car models



Cool White color temperature of 6,500 K

Better visibility thanks to daylight effect



OSRAM's first Plug & Play off-road LED replacement for HID

With extra brightness the OSRAM LEDDriving HL EASY XEN the OSRAM LEDDriving HL EASY XEN ensures a compact LED replacement of conventional high and low beam lamps. These LED retrofit lamps are 12/24V compatible, come with a color temperature of 6,500 K and ensure a broader light distribution: more light¹⁾ allows to see better and therefore react sooner. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant a long lifetime.

Please note: OSRAM LEDDriving HL EASY XEN change is recommended to be carried out by a professional.

¹⁾ compared to minimum ECE R98

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Ficha técnica da família de produto

Dados técnicos

Descrição do produto	Dados Elétricos				Dados fotométricos
	Entrada de energia	Tensão nominal	Potência nominal	Teste de tensão	Fluxo luminoso nominal
LEDDriving HL EASY XEN ≙ D3S	42.0 W	12 V	42 W	13,2 V	5000 lm

Descrição do produto	Tolerância do fluxo luminoso	Physical Attributes & Dimensions	Expectativa de Vida	Informações Ambientais e Regulamentares Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Diâmetro	Lifespan Tc	Identificador primário do artigo	Lista de candidatos substância 1
LEDDriving HL EASY XEN ≙ D3S	±25 %	13.8 mm	5000 hr	4062172421461	Nenhuma substância declarável contida

Descrição do produto	Número da declaração no banco de dados SCIP
LEDDriving HL EASY XEN ≙ D3S	Nenhuma substância declarável contida

Download Data

Arquivo	
	User instruction GPRS_Instruções dos símbolos de segurança

Informações sobre aplicações

Para obter mais informações sobre aplicações e gráficos acesse a ficha técnica do produto.

Retratação

Sujeito a alteração sem prévio aviso. Sempre utilize a versão mais recente.

