OSRAM

LEDriving HLM EASY T19



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



Superior brightness

Allowing a high compatibility and an easy installation.



LED replacement for conventional T19 high and low beam lamps

Reduced glaring thanks to an optimal light distribution



LED high and low beams lamps with plug & play system for motorcycles.

The OSRAM LEDriving HLM EASY represent an easy solution to upgrade conventional motorcycle headlights with cool white LED light – with a color temperature of 6,000 K, they provide a stylish and modern look as well as superior brightness. Equipped with the latest LED technology and a very compact design, these lamps allow high compatibility and an easy installation for a wide range of motorcycle models. The LEDriving HLM EASY lamps are 12V and AC/DC compatible and offer a long service life. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Electrical | Data | | | Photomet | ric Data | | |
|------------------------|------------------|-----------------|---------------------|----------------|-----------------------|-------------|--------------------------------------------------------------------------------------------------------------|--|
| Product description | Power input | Nominal voltage | Nominal wa | ittage | Nominal luminous flux | | Luminous flux tolerance | |
| LEDriving HLM EASY T19 | 4.5 W / 5.5 W | 13.5 V | 5 W | | 600/500 L | m | ±15 % | |
| | Physical Attr | | ibutes & Dimensions | | Lifetime Data | | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | |
| Product description | Diameter | Diamet | er | Lifespan B3 | Lifespan Tc | Primary art | ticle | |
| LEDriving HLM EASY T19 | 18.4 mm | 18.4 mr | n | 500 hr | 1000 hr | 406217234 | • | |

| Product description | Candidate list substance 1 | CAS No. of substance | Safe use instruction | Declaration no. in SCIP database |
|------------------------|----------------------------|----------------------|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| LEDriving HLM EASY T19 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | efa593e8-2c11-4e97- 9734-d514687a1b08 5ec6e727-7f8a- 4bc0-ac15- c8ce50c92a5f |

Product family datasheet

Download Data

File



User instruction
GPRS_Safety symbols instructions

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.